# SAFETY DATA SHEET

AUTOCOLOR

Date of issue/Date of revision

: 2 December 2024

**Version** : 1.05

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: AQUABASE PLUS TRANSPARENT GREEN
Product code	: P991-8952/E1
Product type	: Liquid.
Other means of identification	: Not available.
	₩YFH-H4YF-W00H-P5RR
1.2 Relevant identified us	ses of the substance or mixture and uses advised against
Dreduction	

Product use	: Industrial applications.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

#### **1.3 Details of the supplier of the safety data sheet**

PPG Industries (UK) Ltd. Needham Road, Stowmarket, Suffolk, IP14 2AD, UK Tel: +44 (0) 1449 773 338 PPG Industries Italia S.r.l., Via Comasina, 121, 20161 Milano, Italy Tel: +39 02 6404.1

e-mail address of person : Product.Stewardship.EMEA@ppg.com responsible for this SDS

#### 1.4 Emergency telephone number

#### Supplier

- Company emergency telephone number : +44 (0) 1449 773 338 ( 0900-1600)

### **SECTION 2: Hazards identification**

2.1 Classification of the	substance or mixture
Product definition	: Mixture

Classification according to UK CLP/GHS Not classified.

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> <li>P501</li> </ul>
Supplemental label elements	: Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction. Safety data sheet available on request.

<mark>Code</mark> AQUABA	: P991-8952/E1 SE PLUS TRANSPARENT GREEN	Date of issue/Date of revision	: 2 December 2024
SECTI	ON 2: Hazards identification		

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and	: Not applicable.
articles	
Special packaging requirem	<u>ents</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

### **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Туре
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≥5.0 - ≤7.8	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≥0.10 - ≤2.1	Eye Irrit. 2, H319	[1] [2]
2,4,7,9-tetramethyldec-5-yne- 4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	<1.0	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### SUB codes represent substances without registered CAS Numbers.

Code	: P991-8952/E1	Date of issue/Date of revision	: 2 December 2024
AQUABASE	PLUS TRANSPARENT GREEN		

### **SECTION 4: First aid measures**

4.1 Description of first aid n	neasures
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

Potential acute health	effects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	:/symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	None known.	
5.2 Special hazards arising f	the substance or mixture	
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.	
Hazardous combustion products	Decomposition products may include the following materials: carbon oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incider there is a fire. No action shall be taken involving any personal risk or without suitable training.	nt if

Code : P991-89 AQUABASE PLUS TRA		Date of issue/Date of revision	: 2 December 2024
SECTION 5: Firef	ighting measures		

Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe ha	indling
Protective measures	: Put on appropriate personal protective equipment (see Section 8).
	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Code : P991-8952/E1

Date of issue/Date of revision

: 2 December 2024

AQUABASE PLUS TRANSPARENT GREEN

### **SECTION 7: Handling and storage**

Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
2-butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed
	through skin.
	STEL 15 minutes: 50 ppm.
	TWA 8 hours: 25 ppm.
	STEL 15 minutes: 246 mg/m <sup>3</sup> .
	TWA 8 hours: 123 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020)
	TWA 8 hours: 10 ppm.
	TWA 8 hours: 67.5 mg/m <sup>3</sup> .
	STEL 15 minutes: 15 ppm.
	STEL 15 minutes: 101.2 mg/m <sup>3</sup> .

#### **Biological exposure indices**

Product/ingredient name	Exposure indices
2-butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 8/2018) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres -Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	246 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	426 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/m <sup>3</sup>	Workers	Systemic
2-(2-butoxyethoxy)ethanol	DNEL	Long term Oral	6.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	67.5 mg/m <sup>3</sup>	Workers	Local
English (GB)		United King	gdom (UK)		5/13

Code	: P991-8952/E1	Date of issue/Date of revision	: 2 December 2024
AQUAB/	ASE PLUS TRANSPARENT GREEN		

# SECTION 8: Exposure controls/personal protection

_					
	DNEL	Short term Inhalation	101.2 mg/m <sup>3</sup>	Workers	Local
2,4,7,9-tetramethyldec-5-yne-	DNEL	Long term Oral	0.29 mg/kg bw/day	General population	Systemic
4,7-diol		_			-
	DNEL	Long term Dermal	0.29 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.505 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.812 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	2.86 mg/m <sup>3</sup>	Workers	Systemic

#### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
2-butoxyethanol	Fresh water	8.8 mg/l	Assessment Factors
	Marine water	0.88 mg/l	Assessment Factors
	Fresh water sediment	34.6 mg/kg	Equilibrium Partitioning
	Marine water sediment	3.46 mg/kg	Equilibrium Partitioning
	Soil	3.13 mg/kg	Equilibrium Partitioning
	Sewage Treatment Plant	463 mg/l	Assessment Factors
2-(2-butoxyethoxy)ethanol	Fresh water	1.1 mg/l	Assessment Factors
	Marine water	0.11 mg/l	Assessment Factors
	Sewage Treatment Plant		Assessment Factors
	Fresh water sediment	4.4 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.44 mg/kg dwt	Equilibrium Partitioning
	Soil	0.32 mg/kg dwt	Equilibrium Partitioning
2,4,7,9-tetramethyldec-5-yne-4,7-diol	Fresh water	0.04 mg/l	Assessment Factors
	Marine water	0.004 mg/l	Assessment Factors
	Sewage Treatment Plant	7 mg/l	Assessment Factors
	Fresh water sediment	0.32 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.032 mg/kg dwt	Equilibrium Partitioning
	Soil	0.028 mg/kg dwt	Equilibrium Partitioning

#### 8.2 Exposure controls

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields.
Hand protection	<ul> <li>Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.</li> <li>polyethylene</li> </ul>
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Code	÷	<b>P9</b>
------	---	-----------

91-8952/E1 AQUABASE PLUS TRANSPARENT GREEN Date of issue/Date of revision

: 2 December 2024

### **SECTION 8: Exposure controls/personal protection**

**Environmental exposure** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some controls cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

pH Viscosity	: 8 : Dyn	amic (room tem	perature): Not ava	illable.	
рН	: 8				
2-(2-butoxyethoxy)ethanol		210	410	DIN 51794	
Ingredient name		°C	°F	Method	
Auto-ignition temperature	:				
Flash point	: Clos	sed cup: 100°C	(212°F) [Product c	loes not sustain combustion	.]
Upper/lower flammability or explosive limits	•	available.			
boiling range Flammability (solid, gas)	: liqui	d			
Initial boiling point and	: >37	.78°C (>100°F)			
Melting point/freezing point	:				
Odour threshold	: Not	available.			
Odour	: Fair	nt odour.			
Colour	: Colo	ourless.			
Physical state	: Liqu	iid.			

#### Solubility(ies)

	Media	Result
	cold water	Partially soluble
N	liscible with water : Y	/es.

Partition coefficient: n-octanol/ : Not applicable.

2

ŝ

#### water

Vapour pressure

	V	Vapour Pressure at 20°C		V	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Relative density	: 1.03	3	Į			I	
Explosive properties		•	self is not explosive with air is possible		ition of an e	explosible mixture of	
Oxidising properties Particle characteristics	: Pro	duct does r	not present an oxic	lizing hazard.			

Code AQUABAS	: P991-8952/E1 SE PLUS TRANSPARENT GREEN	Date of issue/Date of revision	: 2 December 2024
SECTIO	N 10, Stability and reactive	i4.,	

SECTION 10: Stabilit	and reactivity	
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredier	nts.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition pro Refer to protective measures listed in sections 7 and 8.	oducts
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.	
10.6 Hazardous decomposition products	Depending on conditions, decomposition products may include the following materials: carbon oxides	

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Vapour	Rat	3 mg/l	4 hours
-	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
2,4,7,9-tetramethyldec- 5-yne-4,7-diol	LC50 Inhalation Dusts and mists	Rat	>20 mg/l	1 hours
-	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	4.6 g/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself. <u>Acute toxicity estimates</u>

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
AQUABASE PLUS TRANSPARENT GREEN	19485.9	N/A	327018.8	46.8	N/A
2-butoxyethanol	1200	N/A	N/A	3	N/A
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
2,4,7,9-tetramethyldec-5-yne-4,7-diol	4600	N/A	N/A	N/A	N/A

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol	Eyes - Irritant	Rabbit	-	24 hours	21 days
	Skin - Moderate irritant	Rabbit	-	4 hours	28 days
2,4,7,9-tetramethyldec-5-yne- 4,7-diol	Eyes - Severe irritant	Rabbit	-	0.1 Mililiters	-
	Skin - Mild irritant	Rabbit	-	0.5 Grams	-
Conclusion/Summary	Not available.				
Skin	There are no data available on	the mixture its	elf.		
Eyes	There are no data available on	the mixture its	elf.		
Respiratory	: There are no data available on	the mixture its	elf.		
Sensitisation					
Conclusion/Summary					

English (GB)

Code : P991-8952/E1	Date of issue/Date of revision : 2 December 2024
AQUABASE PLUS TRANSPA	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
<u>Carcinogenicity</u>	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
<b>Teratogenicity</b>	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxicit	<u>y (single exposure)</u>
Not available.	
Specific target organ toxicit	<u>y (repeated exposure)</u>
Not available.	
Aspiration hazard	
Not available.	
Information on likely routes	: Not available.
of exposure	
Potential acute health effects	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	sical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
•	ts as well as chronic effects from short and long-term exposure
Short term exposure Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
	····

English (GB)

#### Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

Code	: P991-8952/E1	Date of issue/Date of revision	: 2 December 2024
AQUAB	ASE PLUS TRANSPARENT GREEN		

### **SECTION 11: Toxicological information**

Other information

: Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-butoxyethanol	Acute LC50 1474 mg/l Chronic NOEC >100 mg/l	Fish Fish	96 hours 21 days
Conclusion/Summers			·

**Conclusion/Summary** : Not available.

#### 12.2 Persistence and degradability

Conclusion/Summary	: Not available.		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxyethanol	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	Low
2-(2-butoxyethoxy)ethanol	1		Low

#### 12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **13.1 Waste treatment methods**

#### Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### Hazardous waste

#### Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### **Packaging**

Code	: P991-8952/E1	Date of issue/Date of revision	: 2 December 2024
AQUABASE	PLUS TRANSPARENT GREEN		

# SECTION 13: Disposal considerations

Methods of disposal	packaging sh	on of waste should be avoided or minimised wherever possible. Waste ould be recycled. Incineration or landfill should only be considered g is not feasible.
Type of packaging		Waste catalogue
Container	15 01 02	plastic packaging
Special precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

### **SECTION 14: Transport information**

ADR/RID	ADN	IMDG	IATA
Not regulated.	9003	Not regulated.	Not regulated.
-	SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C (2-butoxyethanol, 2- (2-butoxyethoxy) ethanol)	-	-
-	9	-	-
-	-	-	-
No.	No.	No.	No.
Not applicable.	Not applicable.	Not applicable.	Not applicable.
	Not regulated.         -         -         -         -         No.	Not regulated.9003-SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C-(2-butoxyethanol, 2- (2-butoxyethoxy) ethanol)-9No.No.	Not regulated.9003Not regulatedSUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 

- ADN : The product is only regulated as a dangerous good when transported in tank vessels.
- **IMDG** : None identified.
- IATA : None identified.

```
14.6 Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
```

14.7 Transport in bulk	: Not available.
according to IMO	
instruments	

### **SECTION 15: Regulatory information**

15.1 Safety, health and env	ironmental regulations/legislation specific for the substance or mixture
<u>UK (GB)/REACH</u>	
Annex XIV - List of subst	ances subject to authorisation
Annex XIV	
None of the components	are listed.
Substances of very hig	<u>1 concern</u>
None of the components	are listed.
Explosive precursors	: Not applicable.

English (GB)

United Kingdom (UK)

Code	: P991-8952/E1	Date of issue/Date of revision	: 2 December 2024
AQUABASE	PLUS TRANSPARENT GREEN		

# SECTION 15: Regulatory information

#### **Ozone depleting substances**

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
2-(2-butoxyethoxy)ethanol	55 [Consumer paint]

Labelling

: Not applicable.

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and
	Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019
	No. 720 and amendments
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = GB CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification

Not classified.

#### Full text of abbreviated H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H412	Harmful to aquatic life with long lasting effects.

#### **Full text of classifications**

Acute Tox. 3	ACUTE TOXICITY - Category 3		
Acute Tox. 4	ACUTE TOXICITY - Category 4		
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3		
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1		
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2		
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2		
Skin Sens. 1B	SKIN SENSITISATION - Category 1B		
History			
Date of issue/ Date of revision	: 2 December 2024		
Date of previous issue	e : 27 November 2024		
Prepared by	: EHS		
Version	: 1.05		

**Disclaimer** 

Code	:	P991-8952/E1
Code	÷	P991-8952/E1

Date of issue/Date of revision

: 2 December 2024

AQUABASE PLUS TRANSPARENT GREEN

### **SECTION 16: Other information**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.