SAFETY DATA SHEET

AUTOCOLOR

Date of issue/Date of revision

: 2 December 2024

Version : 1.05

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

| 1.1 Product identifier | |
|----------------------------------|---------------------------------|
| Product name | : AQUABASE PLUS FIRESIDE COPPER |
| Product code | : P999-XR16/E0.5 |
| Product type | : Liquid. |
| Other means of identification | : Not available. |
| | ₿ĎJH-Q49K-G00C-6R2J |
| | |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Product use | : Industrial applications. | |
|----------------------------------|---|--|
| Use of the substance/ mixture | : Coating. | |
| Uses advised against | : Product is not intended, labelled or packaged for consumer use. | |

1.3 Details of the supplier of the safety data sheet

PPG Industries (UK) Ltd. Needham Road, Stowmarket, Suffolk, IP14 2AD, UK Tel: +44 (0) 1449 773 338 PPG Industries Italia S.r.l., Via Comasina, 121, 20161 Milano, Italy Tel: +39 02 6404.1

e-mail address of person : Product.Stewardship.EMEA@ppg.com responsible for this SDS

1.4 Emergency telephone number

Supplier

- Company emergency telephone number : +44 (0) 1449 773 338 (0900-1600)

SECTION 2: Hazards identification

| 2.1 Classification of the | substance or mixture |
|---------------------------|----------------------|
| Product definition | : Mixture |

Classification according to UK CLP/GHS Not classified.

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 11 for more detailed information on health effects and symptoms.

| 2.2 Label elements | | |
|--------------------------------|---|---|
| Signal word | 1 | No signal word. |
| Hazard statements | 1 | No known significant effects or critical hazards. |
| Precautionary statements | | |
| Prevention | 1 | Not applicable. |
| Response | 1 | Not applicable. |
| Storage | 1 | Not applicable. |
| Disposal | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| | | P501 |
| Supplemental label elements | : | Safety data sheet available on request. |

| Code : P999-XR16/E0.5 AQUABASE PLUS FIRESIDE COPPER | Date of issue/Date of revision | : 2 December 2024 |
|--|--------------------------------|-------------------|
| SECTION 2: Hazards identification | on | |

| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | Not applicable. | |
|---|---|---|
| Special packaging requirement | <u>its</u> | |
| Containers to be fitted with child-resistant fastenings | Not applicable. | |
| Tactile warning of danger | Not applicable. | |
| 2.3 Other hazards | | |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | This mixture does not contain any substances that are assessed to be a PBT or vPvB. | а |
| Other hazards which do not result in classification | None known. | |

SECTION 3: Composition/information on ingredients

| Product/ingredient name | Identifiers | % | Classification | Туре |
|-------------------------|---|------------|---|---------|
| 2-butoxyethanol | REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0 | ≥5.0 - <10 | Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 | [1] [2] |
| | | | See Section 16 for the full text of the H statements declared above. | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Inhalation Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is 1 irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. : If swallowed, seek medical advice immediately and show the container or label. Keep Ingestion person warm and at rest. Do NOT induce vomiting. **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

| English (GB) | United Kingdom (UK) | 2/11 |
|--------------|---------------------|------|
| | | |

| Code : P999-XR16/ AQUABASE PLUS FIRESIE | | Date of issue/Date of revision | : 2 December 2024 |
|--|---------------------|--|---------------------------|
| SECTION 4: First a | id measures | | |
| Potential acute health effe | <u>cts</u> | | |
| Eye contact | : No known sigi | nificant effects or critical hazards. | |
| Inhalation | : No known sigi | nificant effects or critical hazards. | |
| Skin contact | : No known sigi | nificant effects or critical hazards. | |
| Ingestion | : No known sigi | nificant effects or critical hazards. | |
| Over-exposure signs/syn | nptoms | | |
| Eye contact | : No specific da | ita. | |
| Inhalation | : No specific da | ita. | |
| Skin contact | : No specific da | ita. | |
| Ingestion | : No specific da | ita. | |
| 4.3 Indication of any imme | diate medical atten | tion and special treatment needed | |
| Notes to physician | | natically. Contact poison treatment specia e been ingested or inhaled. | list immediately if large |
| Specific treatments | : No specific tre | eatment. | |
| SECTION 5: Firefig | hting measure | es | |
| 5.1 Extinguishing media | | | |
| Suitable extinguishing media | : Use an exting | uishing agent suitable for the surrounding | fire. |

| Unsuitable extinguishing | : None known. |
|--------------------------|---------------|
| media | |

5.2 Special hazards arising from the substance or mixture

| 3.2 Opecial nazarus arising n | |
|---|---|
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous combustion products | : Decomposition products may include the following materials: carbon oxides metal oxide/oxides |
| 5.3 Advice for firefighters | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, protective equipment and emergency procedures | | | |
|---|---|------|--|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate persona protective equipment. | | |
| For emergency responders | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". | | |
| 6.2 Environmental precautions | : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmen pollution (sewers, waterways, soil or air). | | |
| English (GB) | United Kingdom (UK) | 3/11 | |

| Code | : P999-XR16/E0.5 | Date of issue/Date of revision | : 2 December 2024 |
|---------|------------------------|--------------------------------|-------------------|
| AQUABAS | E PLUS FIRESIDE COPPER | | |

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
|---------------------------------|--|
| Large spill | : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |
| 6.4 Reference to other sections | : See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). |
|--|--|
| | Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. |
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

| Code : P99 | 9-XR16/E0.5 | Date of issue/Date of revision | : 2 December 2024 |
|------------|-------------|--------------------------------|-------------------|
|------------|-------------|--------------------------------|-------------------|

AQUABASE PLUS FIRESIDE COPPER

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Exposure limit values |
|-------------------------|---|
| 2-butoxyethanol | EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed |
| | through skin. |
| | STEL 15 minutes: 50 ppm. |
| | TWA 8 hours: 25 ppm. |
| | STEL 15 minutes: 246 mg/m ³ . |
| | TWA 8 hours: 123 mg/m³. |

Biological exposure indices

| Product/ingredient name | Exposure indices |
|-------------------------|--|
| | EH40/2005 BMGVs (United Kingdom (UK), 8/2018) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift. |
| | Sampling time: post shift. |

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres -Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Туре | Exposure | Value | Population | Effects |
|-------------------------|--|---|--|---|--|
| 2-butoxyethanol | DNEL DNEL DNEL DNEL DNEL DNEL DNEL | Long term Oral Short term Oral Long term Inhalation Long term Inhalation Short term Inhalation Short term Inhalation Short term Inhalation Short term Inhalation | 6.3 mg/kg bw/day 26.7 mg/kg bw/day 59 mg/m ³ 98 mg/m ³ 147 mg/m ³ 246 mg/m ³ 426 mg/m ³ 1091 mg/m ³ | General population General population General population Workers General population Workers General population Workers | Systemic Systemic Systemic Local Local |

PNECs

| Product/ingredient name | Compartment Detail | Value | Method Detail |
|-------------------------|------------------------|------------|--------------------------|
| 2-butoxyethanol | Fresh water | 8.8 mg/l | Assessment Factors |
| | Marine water | 0.88 mg/l | Assessment Factors |
| | Fresh water sediment | 34.6 mg/kg | Equilibrium Partitioning |
| | Marine water sediment | 3.46 mg/kg | Equilibrium Partitioning |
| | Soil | 3.13 mg/kg | Equilibrium Partitioning |
| | Sewage Treatment Plant | 463 mg/l | Assessment Factors |

8.2 Exposure controls

| Appropriate engineering controls | : Good general ventilation should be sufficient to control worker exposure to airborne contaminants. |
|---|---|
| Individual protection measu | <u>95</u> |
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection <u>Skin protection</u> | : Safety glasses with side shields. |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. |

| <mark>Code</mark> AQUABA | : P999-XR16/E0.5 SE PLUS FIRESIDE COPPER | Date of issue/Date of revision | : 2 December 2024 | |
|--|---|--------------------------------|-------------------|--|
| SECTION 8: Exposure controls/personal protection | | | | |

| Gloves | : For prolonged or repeated handling, use the following type of gloves: |
|---------------------------------|---|
| | Recommended: nitrile rubber, butyl rubber |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product an the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| Appearance | |
|----------------|--|
| Physical state | |

| Physical state | : Liquid. | | | |
|---|------------|-------------------|---------------------|----------------------|
| Colour | : Colourle | ess. | | |
| Odour | : Faint oc | lour. | | |
| Odour threshold | : Not ava | ilable. | | |
| Melting point/freezing point | : | | | |
| Initial boiling point and boiling range | : >37.78° | C (>100°F) | | |
| Flammability (solid, gas) | : liquid | | | |
| Upper/lower flammability or explosive limits | : Not ava | ilable. | | |
| Flash point | : Closed | cup: 100°C (212°F |) [Product does not | sustain combustion.] |
| Auto-ignition temperature | : | | | |
| Ingredient name | | °C | °F | Method |
| 2-butoxyethanol | | 230 | 446 | DIN 51794 |

| рН | : 8 |
|-----------|---|
| Viscosity | Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): >21 mm²/s |

÷

Solubility(ies)

| ······································ | |
|---|-------------------|
| Media | Result |
| cold water | Partially soluble |
| Miscible with water | : Yes. |
| Partition coefficient: n-octanol/ water | : Not applicable. |
| Vapour pressure | : |

English (GB)

| Code | : P999-XR16/E0.5 | Date of issue/Date of revision | : 2 December 2024 |
|----------|------------------------|--------------------------------|-------------------|
| AQUABASE | E PLUS FIRESIDE COPPER | | |

SECTION 9: Physical and chemical properties

| | Vapour Pressure at 20°C | | | V | Vapour pressure at 50°C | | |
|--------------------------|-------------------------|-------------|---|----------------|-------------------------|----------------------|--|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method | |
| water | 17.5 | 2.3 | | | | | |
| Relative density | : 1 | | | | | | |
| Explosive properties | | | self is not explosive with air is possible | | ation of an e | explosible mixture o | |
| Dxidising properties | : Pro | duct does r | not present an oxid | dizing hazard. | | | |
| Particle characteristics | | | | | | | |
| Median particle size | : Not | applicable | | | | | |

| SECTION 10: Stability and reactivity | | | | |
|--|---|--|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. | | | |
| 10.2 Chemical stability | : The product is stable. | | | |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. | | | |
| 10.4 Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products Refer to protective measures listed in sections 7 and 8. | | | |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. | | | |
| 10.6 Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides | | | |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|------------------------|---------|-------------|----------|
| | LC50 Inhalation Vapour | Rat | 3 mg/l | 4 hours |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| | LD50 Oral | Rat | 1200 mg/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------------|------------------|-------------------|--------------------------------|-----------------------------------|--|
| AQUABASE PLUS FIRESIDE COPPER | | N/A | 363639.3 | 35.5 | N/A |
| 2-butoxyethanol | | N/A | N/A | 3 | N/A |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--|------------------|-------|---------------------|--------------------|
| 2-butoxyethanol | Eyes - Irritant Skin - Moderate irritant | Rabbit Rabbit | - | 24 hours 4 hours | 21 days 28 days |
| Conclusion/Summary | Not available. | L. | | | |
| Skin | : There are no data available on the mixture itself. | | | | |
| Eyes | : There are no data available on the mixture itself. | | | | |

| 7/11 |
|------|
| |

| Code : P999-XR16/E AQUABASE PLUS FIRESIDE | |
|--|--|
| SECTION 11: Toxico | logical information |
| Respiratory | : There are no data available on the mixture itself. |
| Sensitisation | |
| Conclusion/Summary | |
| Skin | : There are no data available on the mixture itself. |
| Respiratory | : There are no data available on the mixture itself. |
| Mutagenicity | |
| Conclusion/Summary Carcinogenicity | : There are no data available on the mixture itself. |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Reproductive toxicity | |
| Conclusion/Summary <u>Teratogenicity</u> | : There are no data available on the mixture itself. |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Specific target organ toxic | ity (single exposure) |
| Not available. | |
| Specific target organ toxic | ity (repeated exposure) |
| Not available. | <u></u> |
| | |
| Aspiration hazard Not available. | |
| nformation on likely routes of exposure | : Not available. |
| Potential acute health effect | <u>s</u> |
| Eye contact | : No known significant effects or critical hazards. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : No known significant effects or critical hazards. |
| Ingestion | : No known significant effects or critical hazards. |
| Symptoms related to the ph | vsical, chemical and toxicological characteristics |
| Eye contact | : No specific data. |
| Inhalation | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |
| Delayed and immediate effe | cts as well as chronic effects from short and long-term exposure |
| Short term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health eff | i <u>ects</u> |
| Not available. | |
| Conclusion/Summery | . Not available |
| Conclusion/Summary | : Not available. |
| General | : No known significant effects or critical hazards. |

United Kingdom (UK)

English (GB)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

| Code | : P999-XR16/E0.5 | Date of issue/Date of revision | : 2 December 2024 |
|----------|----------------------|--------------------------------|-------------------|
| AQUABASE | PLUS FIRESIDE COPPER | | |
| | | | |

SECTION 11: Toxicological information

Mutagenicity

: No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|------------------------|---------|----------|
| 2-butoxyethanol | Acute LC50 1474 mg/l | Fish | 96 hours |
| | Chronic NOEC >100 mg/l | Fish | 21 days |

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

| Conclusion/Summary | : Not available. | | |
|-------------------------|-------------------|------------|------------------|
| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
| 2-butoxyethanol | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| 2-butoxyethanol | 0.81 | - | Low |

12.4 Mobility in soil

| Soil/water partition coefficient (Koc) | : Not available. |
|--|------------------|
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Waste catalogue

| Waste code | Waste designation | |
|------------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | |
| | | |

Packaging

Product

English (GB)

| Code | : P999-XR16/E0.5 | Date of issue/Date of revision | : 2 December 2024 |
|----------|----------------------|--------------------------------|-------------------|
| AQUABASE | PLUS FIRESIDE COPPER | | |

SECTION 13: Disposal considerations

| Methods of disposal | packaging s | ion of waste should be avoided or minimised wherever possible. Waste hould be recycled. Incineration or landfill should only be considered ng is not feasible. |
|---------------------|---|--|
| Type of packaging | | Waste catalogue |
| Container | 15 01 04 | metallic packaging |
| Special precautions | This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. | |

SECTION 14: Transport information

| ADR/RID | ADN | IMDG | IATA |
|-----------------|---|--|--|
| Not regulated. | 9003 | Not regulated. | Not regulated. |
| - | SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C (2-butoxyethanol) | - | - |
| - | 9 | - | - |
| - | - | - | - |
| No. | No. | No. | No. |
| Not applicable. | Not applicable. | Not applicable. | Not applicable. |
| | Not regulated No. No. | Not regulated.9003-SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C (2-butoxyethanol)-9No.No. | Not regulated.9003Not regulatedSUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C (2-butoxyethanol)9No.No.No. |

- **ADN** : The product is only regulated as a dangerous good when transported in tank vessels.
- IMDG : None identified.

ΙΑΤΑ : None identified.

user

14.6 Special precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not available. according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH Annex XIV - List of substances subject to authorisation Annex XIV None of the components are listed.

Substances of very high concern

None of the components are listed.

Explosive precursors : Not applicable.

Ozone depleting substances

English (GB)

United Kingdom (UK)

| Code | : P999-XR16/E0.5 | Date of issue/Date of revision | : 2 December 2024 |
|----------|----------------------|--------------------------------|-------------------|
| AQUABASE | PLUS FIRESIDE COPPER | | |

SECTION 15: Regulatory information

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Seveso Directive

This product is not controlled under the Seveso Directive.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

| Abbreviations and | ATE = Acute Toxicity Estimate |
|-------------------|---|
| acronyms | GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and |
| | Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 |
| | No. 720 and amendments |
| | DMEL = Derived Minimal Effect Level |
| | DNEL = Derived No Effect Level |
| | EUH statement = GB CLP-specific Hazard statement |
| | N/A = Not available |
| | PBT = Persistent, Bioaccumulative and Toxic |
| | PNEC = Predicted No Effect Concentration |
| | RRN = REACH Registration Number |
| | SGG = Segregation Group |
| | vPvB = Very Persistent and Very Bioaccumulative |

Procedure used to derive the classification

Not classified.

Full text of abbreviated H statements

| H302 | Harmful if swallowed. |
|----------------------|--------------------------------|
| H315 H319 H331 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| 1 | |

Full text of classifications

| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
|---------------|--|
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |

<u>History</u>

| Date of issue/ Date of revision | : 2 December 2024 |
|---------------------------------|--------------------|
| Date of previous issue | : 28 November 2024 |
| Prepared by | : EHS |
| Version | : 1.05 |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.