

SAFETY DATA SHEET

Basecoat WB 14 White high strength

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: Basecoat WB 14 White high strength
SDS code	: S51144

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Industrial use	
	Uses advised against
All other uses	
Product use	: FOR INDUSTRIAL USE ONLY
I.3 Details of the supplier of t	he safety data sheet
Akzo Nobel Car Refini Rijksstraatweg 31 2171 AJ Sassenheim The Netherlands + 31 (0)71 308 6944 www.lesonal.com	shes bv
e-mail address of person responsible for this SDS	: PSRA_SSH@akzonobel.com
I.4 Emergency telephone nun	nber
National advisory body/Pois	on Centre
Telephone number	: +44 (0)344 892 0111
<u>Supplier</u>	
Telephone number	: + 31 (0)71 308 6944

Hours of operation : 24 hours

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition

: Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 5-8-2024	Version : 1.01	
Date of previous issue	: 31-7-2024	1/17	AkzoNobel

SECTION 2: Hazards identification

	-	
2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains triisobutyl phosphate, 1,2-benzisothiazol-3(2H)-one and CMIT/MIT(3:1). May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
Special packaging requirem	ien	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥15 - ≤20	Carc. 2, H351 (inhalation)	-	[1] [*]
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤8.2	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
Copolymer Xi, R36	-	≤1.7	Eye Irrit. 2, H319	-	[1]
triisobutyl phosphate	REACH #: 01-2119957118-32 EC: 204-798-3	<1	Skin Sens. 1, H317	-	[1]
Date of issue/Date of revision	: 5-8-2024		Version : 1.01		
Date of previous issue	: 31-7-2024		2/17	Akzo	Nobe

Basecoat WB 14 White high strength

SECTION 3: Composition/information on ingredients					
			greatents	1	
	CAS: 126-71-6				
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 500 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
CMIT/MIT(3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: C $\geq 0.6\%$ Skin Irrit. 2, H315: $0.06\% \leq C < 0.6\%$ Eye Dam. 1, H318: $C \geq 0.6\%$ Eye Irrit. 2, H319: $0.06\% \leq C < 0.6\%$ Skin Sens. 1, H317: $C \geq 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for	_	
			the full text of the H statements declared		
			above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

Date of issue/Date of revision	: 5-8-2024	Version : 1.01	
Date of previous issue	: 31-7-2024	3/17	AkzoNobel

Basecoat WB 14 White high strength

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains triisobutyl phosphate, 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1). May produce an allergic reaction.

Over-exposure	signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

			5
5.1 Extinguishing media			
Suitable extinguishing media		:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishin media	g	:	None known.
5.2 Special hazards arisi	ng fr	on	n the substance or mixture
Hazards from the substance or mixture		:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products		:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters	\$		
Special protective actio for fire-fighters	ns	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighte	ers	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.



SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for c	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Ensure spraying away from persons. Avoid inhalation of vapour, spray or mist. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.



Basecoat WB 14 White high strength

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.
	STEL: 50 ppm 15 minutes.
	TWA: 25 ppm 8 hours. STEL: 246 mg/m ³ 15 minutes. TWA: 123 mg/m ³ 8 hours.
triisobutyl phosphate	EH40/2005 WELs (United Kingdom (UK), 1/2020). [tributyl phosphate, all isomers] STEL: 5 mg/m ³ 15 minutes. TWA: 5 mg/m ³ 8 hours.

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	е Туре	Exposure	Value	Population	Effects
2-butoxyethanol	DNEL	Long term Oral	6.3 mg/kg	General	Systemic
-		-	bw/day	population	
	DNEL	Short term Oral	26.7 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term	59 mg/m ³	General	Systemic
		Inhalation	-	population	
	DNEL	Long term	98 mg/m³	Workers	Systemic
		Inhalation	_		
	DNEL	Short term	147 mg/m ³	General	Local
		Inhalation	_	population	
	DNEL	Short term	246 mg/m ³	Workers	Local
		Inhalation	_		
	DNEL	Short term	426 mg/m ³	General	Systemic
		Inhalation	_	population	-
	DNEL	Short term	1091 mg/	Workers	Systemic
		Inhalation	m³		
triisobutyl phosphate	DNEL	Long term Oral	2.13 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	2.13 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	4.25 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	8.89 mg/m ³		Systemic
		Inhalation		population	
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/	General	Systemic
e of issue/Date of revision	: 5-8-2024		Version	: 1.01	
te of previous issue	: 31-7-2024		6/17		AkzoNob

SECTION 8: Exposure controls/personal protection

SECTION 6. Exposure controls/personal protection						
		DNEL	Long term Dermal	kg bw/day 0.966 mg/ kg bw/day	population Workers	Systemic
		DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
		DNEL	Long term Inhalation	6.81 mg/m³	Workers	Systemic
	CMIT/MIT(3:1)	DNEL	Long term Inhalation	0.02 mg/m ³	General population	Local
		DNEL	Long term Inhalation	0.02 mg/m ³	Workers	Local
		DNEL	Short term Inhalation	0.04 mg/m ³	General population	Local
		DNEL	Short term Inhalation	0.04 mg/m ³	Workers	Local
		DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
		DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic

PNECs

No PNECs available

Date of previous issue

:31-7-2024

8.2 Exposure controls			
Appropriate engineering controls	: Good general ventile contaminants.	ation should be sufficient to control worker ex	xposure to airborne
Individual protection mea	isures		
Hygiene measures	before eating, smok Appropriate techniq Wash contaminated	rms and face thoroughly after handling chem king and using the lavatory and at the end of ues should be used to remove potentially co d clothing before reusing. Ensure that eyewa close to the workstation location.	the working period. ntaminated clothing.
Eye/face protection	assessment indicate gases or dusts. If c	nplying with an approved standard should be es this is necessary to avoid exposure to liqu contact is possible, the following protection sh nent indicates a higher degree of protection:	id splashes, mists, ould be worn,
Skin protection			
Hand protection		impervious gloves complying with an approv when handling chemical products if a risk as	
	protection class of 6 recommended. Rec When only brief con (breakthrough time Recommended glov	frequently repeated contact may occur, a glo 6 (breakthrough time >480 minutes according commended gloves: Viton ® or Nitrile, thickn ntact is expected, a glove with protection clas >30 minutes according to EN374) is recomm ves: Nitrile, thickness \geq 0.12 mm. eplaced regularly and if there is any sign of da	g to EN374) is ess ≥ 0.38 mm. s of 2 or higher nended.
		r effectiveness of the glove may be reduced l and poor maintenance.	by physical/
	product is the most	ck that the final choice of type of glove select appropriate and takes into account the partic the user's risk assessment.	
Date of issue/Date of revision	: 5-8-2024	Version : 1.01	



SECTION 8: Exposure controls/personal protection

Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

a mormation on basic physica	ıa	nu chen	incai prope	1165			
<u>Appearance</u>							
Physical state	:	Liquid.					
Colour	:	White.					
Odour	: Not available.						
Odour threshold	: Not available.						
Melting point/freezing point	: Not available.						
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)						
Flammability	:	Not ava	ailable.				
Lower and upper explosion limit	:	Not app	olicable.				
Flash point	:	Not ava	ailable.				
Auto-ignition temperature	:						
Ingredient name			°C	°F		Method	
2-butoxyethanol			230	446		DIN 51794	
Decomposition temperature	:	Not ava	ailable.		1		
рН	:	8 [Cond	c. (% w/w):	100%] [DIN EN ⁻	1262]		
Viscosity	:	Kinema	atic: 348 mn	n²/s [DIN EN ISC	0 3219]		
Solubility(ies)	:						
Not available.							
Partition coefficient: n-octanol/ water	:	Not app	olicable.				
Vapour pressure	:						

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	23.8	3.2				
2-butoxyethanol	0.75	0.1				

Relative density

: 1.15 [ISO 8130-2/-3]

Date of issue/Date of revision	: 5-8-2024	Version : 1.01	
Date of previous issue	: 31-7-2024	8/17	AkzoNobel

SECTION 9: Physical and chemical properties

Vapour density	1	Not available.
Particle characteristics		
Median particle size	:	Not applicable.
Percentage of particles with aerodynamic diameter ≤ 10 μm	:	0

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: No specific data.		
10.5 Incompatible materials	: No specific data.		
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.		

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains triisobutyl phosphate, 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1). May produce an allergic reaction. **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Gas.	Mouse	700 ppm	7 hours
-	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
	LC50 Inhalation Vapour	Mouse	3380 mg/m ³	7 hours
	LC50 Inhalation Vapour	Rat	2900 mg/m ³	7 hours
	LD50 Dermal	Guinea pig	230 uL/kg	-
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Mouse	536 mg/kg	-
	LD50 Intraperitoneal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Rat	220 mg/kg	-
	LD50 Intravenous	Mouse	1130 mg/kg	-
	LD50 Intravenous	Rabbit	252 mg/kg	-
	LD50 Intravenous	Rat	307 mg/kg	-
te of issue/Date of revision	: 5-8-2024	Versior	: 1.01	
te of previous issue	: 31-7-2024	9/17		AkzoNobe

SECTION 11: Toxicological information

J					
		LD50 Oral	Guinea pig	1200 mg/kg	-
		LD50 Oral	Mouse	1230 mg/kg	-
		LD50 Oral	Mouse	1167 mg/kg	-
		LD50 Oral	Rabbit	300 mg/kg	-
		LD50 Oral	Rabbit	320 mg/kg	-
		LD50 Oral	Rat	917 mg/kg	-
		LD50 Oral	Rat	250 mg/kg	-
		LD50 Route of exposure unreported	Mouse	1050 mg/kg	-
		LD50 Route of exposure unreported	Rat	917 mg/kg	-
	triisobutyl phosphate	LD50 Oral	Rat	>5 g/kg	-
	1,2-benzisothiazol-3(2H)- one	LD50 Oral	Mouse	1150 mg/kg	-
		LD50 Oral	Rat	1020 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied	21481.8	N/A	N/A	53.7	N/A
2-butoxyethanol	1200	N/A	N/A	3	N/A
1,2-benzisothiazol-3(2H)-one	500	N/A	N/A	N/A	N/A
CMIT/MIT(3:1)	100	50	N/A	N/A	0.05

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation	
2-butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-	
				mg		
	Eyes - Severe irritant	Rabbit	-	100 mg	-	
twiis a but the base bata	Skin - Mild irritant	Rabbit	-	500 mg	-	
triisobutyl phosphate	Eyes - Moderate irritant Skin - Moderate irritant	Rabbit Rabbit	-	100 UI 500 UI	-	
Conclusion/Summary	: Not available.					
Sensitisation						
Conclusion/Summary	: Not available.					
<u>Mutagenicity</u>						
Conclusion/Summary	: Not available.					
<u>Carcinogenicity</u>						
Conclusion/Summary	: Not available.	: Not available.				
Reproductive toxicity						
Conclusion/Summary	: Not available.					
Teratogenicity						
Conclusion/Summary	: Not available.					
<u>Specific target organ toxicit</u>	<u>y (single exposure)</u>					
Not available.						
Specific target organ toxicit	<u>y (repeated exposure)</u>					
Not available.						
Aspiration hazard						
Not available.						



SECTION 11: Toxicological information

Information on likely routes of exposure	:	Not available.
Potential acute health effects	<u>i</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy	sic	al, chemical and toxicological characteristics
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.
	<u>ts</u>	as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>s</u>
Not available.		
Conclusion/Summary	:	Not available.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Date of issue/Date of revision	: 5-8-2024	Version : 1.01	
Date of previous issue	: 31-7-2024	11/17	AkzoNobel

Basecoat WB 14 White high strength

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
rtanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
2-butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
,	Acute LC50 800000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1490000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours
I,2-benzisothiazol-3(2H)-one		Daphnia - Daphnia magna	48 hours
	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm resh water	Daphnia - Pseudomonas putia	16 hours
	Acute IC50 0.067 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 1.3 mg/l	Fish - Ochorhyncus mykiss	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	low

12.4 Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Date of issue/Date of revision	: 5-8-2024	Version : 1.01	
Date of previous issue	: 31-7-2024	12/17	AkzoNobel

Basecoat WB 14 White high strength

SECTION 12: Ecological information

Mobility

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.



SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not applicable. **bulk according to IMO instruments**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB) /REACH</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Other EU regulations		
VOC	:	The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	:	Not available.
Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed



Basecoat WB 14 White high strength SECTION 15: Regulatory information Industrial emissions : Not listed (integrated pollution prevention and control) -Water Ozone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants Not listed. **Seveso Directive** This product is not controlled under the Seveso Directive. **National regulations Biocidal products regulation** International regulations Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed. **Montreal Protocol** Not listed. Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety : No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification		
Not classified.			
Full text of abbroviated H statements			

Full text of abbreviated H statements

Date of issue/Date of revision	: 5-8-2024	Version : 1.01	
Date of previous issue	: 31-7-2024	15/17	AkzoNobel

SECTION 16: Othe	r information	
H301 H302 H310 H314 H315 H317 H318 H319 H330 H331 H351 H400 H410		Toxic if swallowed. Harmful if swallowed. Fatal in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes an allergic skin reaction. Causes serious eye damage. Causes serious eye damage. Causes serious eye irritation. Fatal if inhaled. Toxic if inhaled. Suspected of causing cancer. Very toxic to aquatic life.
H410 EUH071		Very toxic to aquatic life with long lasting effects. Corrosive to the respiratory tract.
Full text of classifications	[CLP/GHS]	
Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Carc. 2 Eye Dam. 1 Eye Irrit. 2 Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A		ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1
Date of printing Date of issue/ Date of revision	: 5-8-2024 : 5-8-2024	
Date of previous issue	: 31-7-2024	
Version	: 1.01	
Notice to reader		

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

IA_413

Date of issue/Date of revision	: 5-8-2024	Version : 1.01	
Date of previous issue	: 31-7-2024	16/17	AkzoNobel

Basecoat WB 14 White high strength

Date of issue/Date of revision
Date of previous issue

